





CLEARANCE SPECIFICATIONS		
Non-combustible:		
	Description	Mino II & Rondo
	Minimum distance to non-combustible material	2" (5 cm)
Note: Non-combustible must be solid cement or block (not brick or tile over combustible material)		
Combustible:		
Minimum distance to combustible material - as shown:		
		
	Description	Mino II & Rondo
A	Sidewall to unit	13" (33cm)
B	Backwall to unit	6.5" (16.5cm)
C	Cornerwall to unit	6" (15.2cm)
D	Sidewall to connector	20" (50.8cm)
E	Backwall to connector	12" (30.5cm)
F	Cornerwall to connector	14" (35.6cm)
G	Ceiling to appliance	43.5" (111cm)
		
H	Backwall to unit	13" (33cm)
I	Backwall to connector	20" (50.8cm)
J	Sidewall to unit	34" (86.4cm)
K	Sidewall to connector	41" (104cm)
L	Distance to frontwall / furnishing	34" (86.4cm)
M	Cornerwall to connector	41" (104cm)


FLOOR PROTECTOR TURNABLE



FLOOR PROTECTOR



** REAR/TOP VENT OPTION



**:
Please refer to NFPA guide-
lines in USA and CAN/CSA
B365-M91 in Canada.