









Technical data and specifications:

	RAIS Rondo Page 6	RAIS Mino II Page 7	RAIS Vola Page 8	RAIS Gabo Page 9	RAIS Classic 106 Page 10	RAIS Pina Page 11	RAIS Bando Page 12	RAIS Malta Page 13	RAIS Komba Page 14	RAIS Arena Page 15	RAIS Atlas Page 16	RAIS Bora Page 17	Rais 60 Page 19
													
													
Technical Data													
Heat													
Optimal heat output	17,1 kBTU	17,1 kBTU	15,4 kBTU	15,4 kBTU	27,3 kBTU	15,4 kBTU	23,9 kBTU	23,9 kBTU	27,3 kBTU	27,3 kBTU	27,3 kBTU	23,9 kBTU	23,9 kBTU
Heat range (min. - max.)	11,5-22,6 kBTU	11,5-22,6 kBTU	12,1-26,7 kBTU	12,1-26,7 kBTU	20,5-40,9 kBTU	12,1-26,7 kBTU	6,8-27,3 kBTU	6,8-27,3 kBTU	13,6-34,1 kBTU	13,6-34,1 kBTU	13,6-34,1 kBTU	6,8-27,3 kBTU	10,2-27,3 kBTU
Heating capacity (at -4°F/20°C)	1100 sq.ft	1100 sq.ft	861 sq.ft	861 sq.ft	1292 sq.ft	861 sq.ft	1076 sq.ft	1076 sq.ft	1292 sq.ft	1292 sq.ft	1292 sq.ft	1076 sq.ft	1076 sq.ft
Measurements													
Stove exterior (W-D-H)	19 ¹ / ₂ -19 ¹ / ₂ -40 ¹ / ₂ inches	20-18-39 ⁵ / ₈ inches	20 ⁷ / ₈ -16 ⁵ / ₈ -46 ⁷ / ₈ inches	20 ¹ / ₈ -18 ³ / ₈ -39 ⁵ / ₈ inches	25 ¹ / ₈ -19 ⁵ / ₈ -41 ³ / ₈ inches	21 ³ / ₈ -17 ⁷ / ₈ -44 ¹ / ₈ inches	21 ¹ / ₄ -20-43 ³ / ₄ inches	20 ⁷ / ₈ -20 ¹ / ₄ -42 ³ / ₈ inches	24 ³ / ₈ -22-43 ¹ / ₄ inches	22 ⁵ / ₈ -21 ³ / ₈ -43 ¹ / ₂ inches	22 ⁷ / ₈ -21 ³ / ₈ -42 ¹ / ₂ inches	22 ¹ / ₂ -21 ⁵ / ₈ -43 ⁷ / ₈ inches	27 ¹ / ₂ -17 ⁵ / ₈ -22 ⁵ / ₈ inches
Firebox interior (W-D-H)	13 ¹ / ₈ -11 ¹ / ₈ -13 ³ / ₈ inches	13 ¹ / ₈ -11 ⁷ / ₈ -13 ³ / ₈ inches	14 ¹ / ₄ -9 ⁵ / ₈ -14 ¹ / ₂ inches	14 ¹ / ₄ -9 ⁵ / ₈ -14 ¹ / ₂ inches	17 ⁷ / ₈ -15 ¹ / ₄ -14 ¹ / ₈ inches	14 ³ / ₄ -9 ⁵ / ₈ -14 ¹ / ₂ inches	14 ¹ / ₈ -13 ³ / ₄ -14 ¹ / ₈ inches	14 ¹ / ₈ -13 ³ / ₄ -14 ¹ / ₈ inches	15 ⁵ / ₈ -16 ⁷ / ₈ -16 ¹ / ₂ inches	15 ⁵ / ₈ -16 ⁷ / ₈ -16 ¹ / ₂ inches	15 ⁵ / ₈ -16 ⁷ / ₈ -16 ¹ / ₂ inches	14 ¹ / ₈ -13 ³ / ₄ -14 ¹ / ₈ inches	20 ⁷ / ₈ -13-13 ³ / ₄ inches
Pipe diameter	6 inches	6 inches	6 inches	6 inches	6 inches	6 inches	6 inches	6 inches	6 inches	6 inches	6 inches	6 inches	6 inches
Distance to combustible side wall A	13 inches	13 inches	11 inches	11 inches	19 inches	11 inches	19 inches	19 inches	17 inches	18 inches	18 inches	18 inches	÷
Distance to combustible back wall B	6 ¹ / ₂ inches	6 ¹ / ₂ inches	6 inches	6 inches	11 inches	6 inches	6 ¹ / ₂ inches	5 ¹ / ₂ inches	9 inches	10 inches	9 inches	4 ¹ / ₂ inches	÷
Distance from center of top exit to the back edge of the top plate C	10 inches	8 ⁵ / ₈ inches	5 inches	5 inches	1 ¹ / ₂ inches	5 inches	3 ¹ / ₂ inches	4 ¹ / ₂ inches	4 inches	3 inches	4 inches	5 ¹ / ₂ inches	÷
Minimum size of built-in opening (W-D-H)	÷	÷	÷	÷	÷	÷	÷	÷	÷	÷	÷	÷	29 ¹ / ₈ -18 ¹ / ₂ -23 ¹ / ₄ inches
Frame (W-H)	÷	÷	÷	÷	÷	÷	÷	÷	÷	÷	÷	÷	29 ¹ / ₂ -25 ⁵ / ₈ inches
Distance to a combustible adjacent sidewall	÷	÷	÷	÷	÷	÷	÷	÷	÷	÷	÷	÷	12 inches
Distance to a combustible mantel	÷	÷	÷	÷	÷	÷	÷	÷	÷	÷	÷	÷	16 inches
Distances													
Top vent height - floor to exit in top plate	38 ³ / ₄ inches	38 ³ / ₄ inches	44 ³ / ₄ inches	38 ⁵ / ₈ inches	41 ¹ / ₄ inches	42 inches	40 ³ / ₄ inches	40 ³ / ₄ inches	41 ¹ / ₂ inches	41 ¹ / ₂ inches	41 ¹ / ₂ inches	41 ¹ / ₂ inches	
Rear vent height - floor to center of rear exit	34 ³ / ₄ inches	34 ³ / ₄ inches			36 ¹ / ₄ inches		35 ⁵ / ₈ inches	35 ⁵ / ₈ inches	36 ¹ / ₄ inches	36 ¹ / ₄ inches	36 ¹ / ₄ inches	36 ¹ / ₄ inches	
Center pipe in top to back edge of stove	9 ³ / ₈ inches	8 inches	6 ⁷ / ₈ inches	5 inches	4 ⁷ / ₈ inches	7 ¹ / ₄ inches	6 ⁷ / ₈ inches	7 ¹ / ₈ inches	5 ⁷ / ₈ inches	6 ⁷ / ₈ inches	6 inches	8 ³ / ₄ inches	
Floor to center of outside air connector (Ø 4"/100 mm)	4 ³ / ₄ inches	4 ³ / ₄ inches	6 ⁷ / ₈ inches	4 ³ / ₄ inches			6 ⁷ / ₈ inches	6 ⁷ / ₈ inches	6 ⁷ / ₈ inches			4 ³ / ₄ inches	
Weight													
- stove	278 lb.	265 lb.	331 lb.	309 lb.	441 lb.	309 lb.	507 lb.	353 lb.		419 lb.		408 lb.	225 lb.
- soapstone top plate	55 lb.	66 lb.	31 lb.	77 lb.				77 lb.		77 lb.			
- stove with soapstone side plates									661 lb.		595 lb.		

Specifications	Standard	Accessory	Standard	Accessory	Standard	Accessory	Standard	Accessory	Standard	Accessory	Standard	Accessory	Standard	Accessory	Standard	Accessory	Standard	Accessory	Standard	Accessory	Standard	Accessory	Standard	Accessory	Standard	Accessory
Steel side plates	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐
Steel top plate	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐
Baking compartment with soapstone	☒	☐	☐	☒	☐	☐	☐	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐
Baking compartment with door	☐	☐	☐	☐	☐	☐	☐	☐	☒	☐	☐	☐	☐	☐	☒	☐	☒	☐	☒	☐	☐	☒	☐	☐	☐	☐
Convection grate (Same color as stove)	☐	☐	☐	☐	☐	☐	☒	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
Convection grate in stainless steel	☐	☐	☐	☐	☐	☒	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☒	☐	☐	☐
Glass-pane door	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐
Air-cooled handle	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐
Shaker grate	☐	☐	☐	☐	☐	☐	☐	☐	☒	☐	☐	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☐	☐
Ash pan	☐	☐	☐	☐	☐	☐	☐	☐	☒	☐	☐	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☐	☐
Color: Black or gray	☒	☐	☒	☐	☒	☐	☒	☐	☐	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐
Top vent exit	☐	☐	☐	☐	☒	☐	☒	☐	☐	☐	☒	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
Top or rear smoke exit	☒	☐	☒	☐	☐	☐	☐	☐	☒	☐	☐	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐	☒	☐
Soapstone top plate	☐	☒	☐	☒	☐	☐	☐	☒	☐	☐	☐	☐	☐	☐	☐	☒	☐	☒	☐	☒	☐	☐	☐	☐	☐	☐
Turnable with turnable connecting pipe	☐	☒	☐	☐	☐	☐	☐	☒	☐	☐	☐	☒	☐	☒	☐	☒	☐	☐	☐	☐	☐	☐	☐	☒	☐	☐
Air system	☒	☐	☐	☒	☐	☒	☐	☒	☐	☐	☐	☐	☐	☒	☐	☒	☐	☐	☐	☐	☐	☐	☒	☐	☐	☐
Portable log holder	☐	☐	☐	☐	☒	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐
Screen	☐	☐	☐	☐	☐	☐	☐	☐	☒	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐	☐