

RAIS Gabo Gas II

On cold winter evenings or warm summer nights – most people have stared into the flickering flames of an open fire, as fascinated as the first humans when they discovered how to make fire thousands of years ago. Many writers and poets have found their inspiration by staring into the flames or the embers of a fire.

Today we no longer have to rely on fires for heating our houses or cooking our meals, but the pleasant heat and the feeling of cozyness is something that we still long for. The free-standing Gabo Gas II stove from Rais can create that mood safely and easily enhanced by its design and qualities making it a valuable asset in any home.

Its design and general qualities makes it a valuable asset in any home.



RAIS Gabo Gas II

embers and burns with a natural fire. It is safe and clean to use, and unlike real logs, gas burning does not create heat adjustment a very simple matter.

The Gabo Gas II has been designed according to the best of the Rais traditions where design, quality, functionality and safety are the four cornerstones of all our production.









RAIS Gabo Gas II Grey



RAIS Gabo Gas II with convection grate in stainless steel



RAIS Gabo Gas II with soapstone top Simple and easy operation

Versatility:

This beautiful stove is available in black or grey Swedish steel and comes with an optional soapstone plate.


Easy to use, the RAIS Gabo Gas II has a large curved glass front that offers a perfect view to the flames. Whichever model you choose, you will have low maintenance and no dirty ashes to remove.

Installation:

The stove can be shipped for use with natural gas but can be easily converted for use with propane (LPG). Typical heat output will range from 13,000 (min.) to 20,000 (max.) BTU/Hour.

Whether it is top or back vented, the RAIS Gabo Gas II requires only a 2 inch clearance to the back wall and a 6 inch clearance to the side walls.





Specifications:	Standard	Accessories	
Steel side plates	Ø	0	
Steel top plate	Ø	0	
Convection grate (Same color as s	tove)	0	
Glass-pane door	Ø	0	
Color: Black or grey	Ø	0	
Top or rear vent exit	Ø	0	
Soapstone top plate	0	Ø	
Stainless steel convection grate	0	Ø	

Technical data	abo Gas II				
Heat					
Typical heat output range	13	-20 kB	TU	4 - 6	kW
Heat imput (min max.)	21 -	31 kB	TU	6 - 9	kW
Measurements					
Stove exterior (W-D-H) 2	0x181/8x391	3/ ₁₆ inc	hes	508x450x1010	mm
Distances					
Center of top exit to back side of to	op plate	6¹/ ₈ inc	hes	156	mm
Floor to center of rear exit	34	.1/ ₁₆ inc	hes	865	mm
Weight					
Stove	2	207	lb.	94	kg
Soanstone top plate		77	lh	35	ka





Refinement Affection Innovation Safety





— THE ORIGINAL —

- THE ORIGINAL -